

Poly Dry and Wet / Dry

The hazardous waste vacuums are shipped with a HEPA filter, 2 ply intermediate pre-filter, 2 ply disposable paper filter bags and 6 mil poly bags with OSHA markings.

DAF dry models include 1 1/2" dry tool kit and WAF wet/dry models a wet/dry tool kit.

Motor Head Assemblies

Durable steel or cast aluminum with choice of 1.3, or 2.3 HP motors. Equipped with 30 Ft, 3 wire grounded safety yellow line cord.

Steel Conversion Adaptor

Holds the HEPA filter on the poly vacuum for dry and wet/dry and on the steel vacuums for wet/dry operation.

Hose Fitting

Positive locking with 360° swivel.

Rotationally Molded Tank

High impact plastic, won't leak or dent and resist chemical attack.

Ball Bearing Swivel Casters

7, 8 and 16 gallon tanks are equipped with 2 1/2" casters and the 20 gallon poly tank with 3" casters.



P41515WAF



1 1/2" Tool Kit Includes:

- 10 Ft Vinyl Hose
- Swivel Hose Connector
- 5 Ft Metal Wand
- 14" Metal Carpet Tool
- 14" Floor Brush
- 11" Plastic Crevice Tool
- 14" Metal Squeegee*
- 6" Upholstery Tool

*Wet Kit Only

specifications

1.3 HP Models

Vacuum Motor:
120 Volt, 2 Stage By-Pass;
94 CFM - Waterlift 84"
Current: 7.5 AMPS
Sound Level: 78dB
Power Cord:
30 Ft, 18/3 Wire Grounded

P4810DAF Dry (310069)

Poly Tank Recovery Capacity:
8 Gallon Wet / 1.10 Bushel Dry

P41510DAF Dry (310190)

Poly Tank Recovery Capacity:
16 Gallon Wet / 2.00 Bushel Dry

P41510WAF Wet/Dry (309087)

Poly Tank Recovery Capacity:
16 Gallon Wet / 2.00 Bushel Dry

2.3 HP Models

Vacuum Motor:
120 Volt, 2 Stage By-Pass;
115 CFM - Waterlift 110"
Current: 11.0 AMPS
Sound Level: 77dB
Power Cord:
30 Ft, 14/3 Wire Grounded

P4815DAF Dry (310093)

Poly Tank Recovery Capacity:
8 Gallon Wet / 1.1 Bushel Dry

P41515DAF Dry (310212)

Poly Tank Recovery Capacity:
16 Gallon Wet / 2.00 Bushel Dry

P41515WAF Wet/Dry (309907)

Poly Tank Recovery Capacity:
16 Gallon Wet / 2.00 Bushel Dry

EnviroMaster™ 7 Dry HEPA

Easy to carry and transport, this compact vac is suited for cleanup in small and confined areas.

The filter system consists of a certified absolute 12" HEPA filter, intermediary 2 ply micro filter and 2 ply disposable filter bag.

The HEPA filter has a minimum efficiency rating of 99.97% at 0.3 microns HOT DOP method certified @ 100 CFM.

The tank is rotationally molded, of high impact plastic with 1/4" wall constructions. No-tip base design has low center of gravity.

Equipped with four 2 1/2" swivel casters and three heavy-duty chrome plated spring steel hold-down clamps to ensure a positive vacuum seal.

Vacuums are shipped with HEPA filter, 2 ply disposable paper filter bag (5/Pk), 2 ply intermediate pre-filter (2/Pk) and dry tool kit.



P4710DAF

specifications

Vacuum Motor:
120 Volt, 2 Stage 1.3 HP By-Pass;
94 CFM - Waterlift 84"; 7.5 AMPS
Sound Level: 78dB
Recovery Capacity: .70 Bu Dry
Power Cord:
30 Ft, 18/3 Wire Grounded

P4710HVAF Dry (369888)

includes 1 1/4" Dry Tool Kit
Tool Kit Includes:

P4710DAF Dry (369861)

includes 1 1/2" Dry Tool Kit